

Page 1/7

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

1 Identification

- · Product identifier
- · Trade name: Flux-Gel Multifix 450-01
- · Application of the substance / the mixture Soldering flux
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Stannol GmbH & Co. KG Haberstrasse 24 D-42551 Velbert
- +49 (0) 2051 3120 332 sdb@stannol.de
- · Information department: Product Safety Department
- Emergency telephone number:

8:00 am - 5:00 pm (CET) +49 (0) 2051 3120 332

+1 (307) 899 3845

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS07

- · Signal word Warning
- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

Precautionary statements

Avoid breathing fume.

If on skin: Wash with plenty of soap and water.

If eye irritation persists: Get medical advice/attention.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 1 Reactivity = 0

Other hazards

Inhalation of vapors that are released during the soldering process should be avoided. Flux fumes will irritate nose, throat and lungs and may cause allergic reaction (asthma) after prolonged or repeated exposure. Therefore, we recommend the usage of fume extractions with appropriate filters.

Always wash your hands carefully with soap and water after handling the product before eating, drinking and smoking. Keep out of reach of children.

- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.

US



Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

Trade name: Flux-Gel Multifix 450-01

(Contd. of page 1)

Page 2/7

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 8000-41-7 Terpineol

EINECS: 232-268-1

CAS: 141-82-2 malonic acid

EINECS: 205-503-0

4 First-aid measures

· Description of first aid measures

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

CAS: 141-82-2 malonic acid 20 mg/m³

PAC-2:

CAS: 141-82-2 malonic acid

230 mg/m³ (Contd. on page 3)

US



Page 3/7

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

Trade name: Flux-Gel Multifix 450-01

(Contd. of page 2)

PAC-3:

CAS: 141-82-2 malonic acid 590 mg/m³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

· Protection of hands:



Protective gloves

Rubber gloves

Synthetic gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)



Page 4/7

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

Trade name: Flux-Gel Multifix 450-01

(Contd. of page 3)

· Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty
Color: Light brown
Odor: Characteristic
Odor threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** Undetermined.

• Flash point: $> 93 \, ^{\circ}\text{C} \, (> 199.4 \, ^{\circ}\text{F})$

Flammability (solid, gaseous): Not applicable.Decomposition temperature: Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

Vapor pressure: Not determined.

• **Density at 20 °C (68 °F):** 0.815 g/cm³ (6.8012 lbs/gal)

Relative density
Vapor density
Evaporation rate
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC content: 0.00 %

· Other information No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.



Page 5/7

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

Trade name: Flux-Gel Multifix 450-01

(Contd. of page 4)

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)



Page 6/7

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

Trade name: Flux-Gel Multifix 450-01

(Contd. of page 5)

· Uncleaned packagings:

· Recommendation: Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· UN-Number

· DOT, ADN, IMDG, IATA not regulated

· UN proper shipping name

· DOT, ADN, IMDG, IATA not regulated

· Transport hazard class(es)

· DOT, ADN, IMDG, IATA

· Class not regulated

· Packing group

DOT, IMDG, IATA not regulated
 Environmental hazards: Not applicable.
 Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation": not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.



Page 7/7

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023 Reviewed on 11/30/2023

Trade name: Flux-Gel Multifix 450-01

(Contd. of page 6)

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

Precautionary statements

Avoid breathing fume.

If on skin: Wash with plenty of soap and water.

If eye irritation persists: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product Safety Department

· Contact: Hr. Dörr

Date of preparation / last revision 11/30/2023

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A