

Page 1/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Flux 900-2-i
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Technical function soldering
- · Application of the substance / the mixture Soldering flux
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Stannol GmbH & Co. KG

Haberstrasse 24

D-42551 Velbert

+49 (0) 2051 3120 332

sdb@stannol.de

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

8:00 am - 5:00 pm (CET) +49 (0) 2051 3120 332

National Poisons Information Service

+44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- $\cdot$  Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Orange juice oil

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.



Page 2/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Trade name: Flux 900-2-i

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3 Other hazards

Flux / flux gels:

Inhalation of vapors released during the soldering process should be avoided. Flux vapors irritate the nose, throat, and respiratory tract, and can lead to allergic reactions (asthma) after prolonged or repeated contact. Therefore, an active suction is recommended.

After working with the product and before eating, drinking or smoking, wash your hands with soap and water. Keep out of the reach of children.

Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64-17-5 ethanol Flam. Liq. 2, H225 60 - 95% Eye Irrit. 2, H319

CAS: 8028-48-6 Orange juice oil Flam. Liq. 3, H226 2 - 9%

EINECS: 232-433-8 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Skin Irrit. 2, H315; Skin Sens. 1, H317

CAS: 124-04-9 adipic acid Eye Irrit. 2, H319 ≤ 1%

EINECS: 204-673-3

CAS: 505-48-6 suberic acid Eye Irrit. 2, H319 ≤ 1%

EINECS: 208-010-9

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Page 3/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Trade name: Flux 900-2-i

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

## · 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

## · 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- $\cdot \ \ \, \text{Further information about storage conditions:}$

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 64-17-5 ethanol

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.



Page 4/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Trade name: Flux 900-2-i

(Contd. of page 3)

#### · Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

#### · Hand protection



Solvent resistant gloves

Rubber gloves

Synthetic rubber gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses

## **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Fluid · Colour: Clear · Odour: Characteristic

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 78 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

· Flash point: 14 °C

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined. Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. Not determined. · Vapour pressure:

· Density and/or relative density

· Density: Not determined. Relative density Not determined.

(Contd. on page 5)



Page 5/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Trade name: Flux 900-2-i

(Contd. of page 4)

· Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

 Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 93.0 % · VOC (EC) 93.00 %

· Change in condition · Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void **Pyrophoric solids** Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 64-17-5 ethanol

Oral LD50 7,060 mg/kg (rat) Inhalative LC50/4 h 20,000 mg/l (rat)

· Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 6)



Page 6/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Trade name: Flux 900-2-i

(Contd. of page 5)

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Packagings that may not be cleansed are to be disposed of in the same manner as the product.

#### **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1993

· 14.2 UN proper shipping name

· ADR 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL

ALCOHOL))

3

· IMDG FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL))

· IATA FLAMMABLE LIQUID, N.O.S. (ETHANOL)

· 14.3 Transport hazard class(es)

· ADR. IMDG. IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 7)



Page 7/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Ш

Trade name: Flux 900-2-i

(Contd. of page 6)

· 14.4 Packing group

· ADR, IMDG, IATA

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code):
 EMS Number:
 Stowage Category
 33
 F-E,S-E
 B

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code D/E

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL

ALCOHOL)), 3, II

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02

G11007

- · Signal word Danger
- · Hazard-determining components of labelling:

Orange juice oil

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

(Contd. on page 8)



Page 8/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2023 Version number 3.4 (replaces version 3.3) Revision: 19.01.2023

Trade name: Flux 900-2-i

(Contd. of page 7)

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

### · Department issuing SDS: Product Safety Department

· Contact: Hr. Dörr

## Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of

Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB