

Page 1/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Flux X33F-07i

Flux X33S-07i

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Technical function soldering
- · Application of the substance / the mixture Soldering flux
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Stannol GmbH & Co. KG Haberstrasse 24 D-42551 Velbert

+49 (0) 2051 3120 332 sdb@stannol.de

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

8:00 am - 5:00 pm (CET) +49 (0) 2051 3120 332

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





G....GG\_

- · Signal word Danger
- · Hazard-determining components of labelling:

propan-2-ol

**Hazard statements** 

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)



Page 2/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i

Flux X33S-07i

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337+P313

Store in a well-ventilated place. Keep cool. P403+P235

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

Flux / flux gels:

Inhalation of vapors released during the soldering process should be avoided. Flux vapors irritate the nose, throat, and respiratory tract, and can lead to allergic reactions (asthma) after prolonged or repeated contact. Therefore, an active suction is recommended.

After working with the product and before eating, drinking or smoking, wash your hands with soap and water. Keep out of the reach of children.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 67-63-0 propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 80 - 100%

EINECS: 200-661-7

CAS: 124-04-9 adipic acid ≤ 2.5% Eye Irrit. 2, H319

EINECS: 204-673-3

Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.



Page 3/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i

Flux X33S-07i

(Contd. of page 2)

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

· Hand protection



Protective gloves

Solvent resistant gloves Rubber gloves



Page 4/8

(Contd. of page 3)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i Flux X33S-07i

Synthetic rubber gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Safety glasses

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Clear
Characteristic
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling range 82 °C

· Flammability Highly flammable.

Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

Flash point: 12 °C

Decomposition temperature: Not determined.pH Not determined.

Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.

· 9.2 Other information

· Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

(Contd. on page 5)



Page 5/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i

Flux X33S-07i

(Contd. of page 4)

· Solvent content:

97.0 % · Organic solvents: · VOC (EC) 96.96 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

### CAS: 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat) LD50 12,800 mg/kg (rabbit) Dermal

Inhalative LC50/4 h 30 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

CAS: 95-14-7 benzotriazole

List II

(Contd. on page 6)



Page 6/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i

Flux X33S-07i

(Contd. of page 5)

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1219

14.2 UN proper shipping name

· ADR
 · IMDG, IATA
 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) mixture
 ISOPROPANOL (ISOPROPYL ALCOHOL) mixture

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 33
 EMS Number: F-E,S-D
 Stowage Category B

· 14.7 Maritime transport in bulk according to IMO

**instruments** Not applicable.

(Contd. on page 7)



Page 7/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i

Flux X33S-07i

(Contd. of page 6)

· Transport/Additional information:

**ADR** 

Limited quantities (LQ)Excepted quantities (EQ)1LCode: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) MIXTURE,

3, II

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

Signal word Danger

· Hazard-determining components of labelling:

propan-2-ol

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 8)



Page 8/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023 Version number 1.4 (replaces version 1.3) Revision: 23.01.2023

Trade name: Flux X33F-07i

Flux X33S-07i

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product Safety Department
- · Contact: Hr. Dörr

## Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB