

Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.03.2023

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Lotpaste SP2200 Sn63Pb37
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Technical function soldering
- \cdot Application of the substance / the mixture $\mbox{Brazing alloy}$
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Stannol GmbH & Co. KG Haberstrasse 24 D-42551 Velbert

+49 (0) 2051 3120 332 sdb@stannol.de

 Further information obtainable from: Product Safety Department
 1.4 Emergency telephone number: 8:00 am - 5:00 pm (CET) +49 (0) 2051 3120 332

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008				
Eye Dam. 1	H318	Causes serious eye damage.		
Repr. 1A	H360FD-H362	May damage fertility. May damage the unborn child. May cause harm to breast-fed children.		
STOT RE 1	H372	Causes damage to the central nervous system, the kidneys and the blood through prolonged or repeated exposure.		
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.		
. 2.2.1 abol elements				

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

lead powder [particle diameter < 1 mm]

2-(2-hexyloxyethoxy)ethanol

Hazard statements

H318 Causes serious eye damage.

H360FD-H362 May damage fertility. May damage the unborn child. May cause harm to breast-fed children.

H372 Causes damage to the central nervous system, the kidneys and the blood through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.



Page 2/9

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

(Contd. of page 1)

Trade name: Lotpaste SP2200 Sn63Pb37

Printing date 29.03.2023

	(Conta. of page 1)			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P263	Avoid contact during pregnancy and while nursing.			
P270	Do not eat, drink or smoke when using this product.			
P273	Avoid release to the environment.			
P280	Wear protective gloves / eye protection.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and			
	easy to do. Continue rinsing.			
P310	Immediately call a doctor.			
P308+P313	IF exposed or concerned: Get medical advice/attention.			
P314	Get medical advice/attention if you feel unwell.			
P391	Collect spillage.			
P405	Store locked up.			
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.			
Additional information:				
EUH201A Warning! Contains lead.				
Bestricted to professional users.				

Restricted to professional users.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

• vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

	•				
,	· Dangerous components:				
	CAS: 7439-92-1	lead powder [particle diameter < 1 mm]	10 - 35%		
	EINECS: 231-100-4	Repr. 1A, H360FD-H362; STOT RE 1, H372 Aquatic Chronic 1, H410			
		EUH201A			
		Specific concentration limit: Repr. 1A; H360D: $C \ge 0.03 \%$			
	CAS: 112-59-4	2-(2-hexyloxyethoxy)ethanol	2 - 9%		
	EINECS: 203-988-3	Eye Dam. 1, H318 Acute Tox. 4, H312			
	CAS: 144413-22-9	complex mixture of Chinese gum rosin post reacted with acrylic acid	2 - 9%		
	ELINCS: 434-230-1	Aquatic Chronic 4, H413			
		Diisooctylamin	≤ 1%		
		Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314			
		Aquatic Chronic 1, H410			
		Acute Tox. 4, H302			
	CAS: 61788-95-2	Amine, (hydrierte Talg-alkyl)dimethyl-	≤ 1%		
	EINECS: 263-022-1	Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410			
	CAS: 3234-02-4	2,3-dibromo-2-butene-1,4-diol	≤ 1%		
	EINECS: 221-779-5	Acute Tox. 3, H301			
	SVHC				

SVHC

CAS: 7439-92-1 lead powder [particle diameter < 1 mm]

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

(Contd. of page 2)

Trade name: Lotpaste SP2200 Sn63Pb37

Printing date 29.03.2023

· After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep container tightly sealed.

• Storage class: 6.1 D

· 7.3 Specific end use(s) No further relevant information available.

GB (Contd. on page 4)



Page 4/9

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

Printing date 29.03.2023

Trade name: Lotpaste SP2200 Sn63Pb37

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 7439-92-1 lead powder [particle diameter < 1 mm]

BOELV (EU) Long-term value: 0.15 mg/m³ as Pb

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

• Appropriate engineering controls No further data: see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Hand protection



Protective gloves

Rubber gloves

Synthetic rubber gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Fluid

Grey

Characteristic

Not determined.

Undetermined.

· Eye/face protection Safety glasses

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- · Colour:
- · Odour:
- · Odour threshold:
- · Melting point/freezing point:
- · Boiling point or initial boiling point and boiling range Undetermined.



Printing date 29.03.2023

Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

Trade name: Lotpaste SP2200 Sn63Pb37

	(Contd. of page 4)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
Kinematic viscosity	
Dynamic:	Not determined.
Solubility	
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value) Vanour processor at 070 °C	Not determined. 1.3 hPa
 Vapour pressure at 970 °C: Vapour pressure: 	1.5 IIFa
· Density and/or relative density	
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance: · Form:	Pasty
· Important information on protection of health and	
environment, and on safety.	•
· Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	· ·
· VOC (EC)	0.00 %
· Solids content:	100.0 %
Change in condition	
· Evaporation rate	Not determined.
 Information with regard to physical hazard classes 	
Explosives	Void
· Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
· Gases under pressure	Void
 Flammable liquids Flammable solids 	Void
· Self-reactive substances and mixtures	Void Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

 \cdot 10.1 Reactivity No further relevant information available.



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Trade name: Lotpaste SP2200 Sn63Pb37

· 10.2 Chemical stability

Printing date 29.03.2023

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 112-59-4 2-(2-hexyloxyethoxy)ethanol

Oral LD50 4,920 mg/kg (rat)

Dermal LD50 1,500 mg/kg (rabbit)

· Serious eye damage/irritation Causes serious eye damage.

• Reproductive toxicity May damage fertility. May damage the unborn child. May cause harm to breast-fed children. • STOT-repeated exposure

Causes damage to the central nervous system, the kidneys and the blood through prolonged or repeated exposure. 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 Butylated hydroxytoluene

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

• **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 7)

GB

Page 6/9

List II

(Contd. of page 5)

Revision: 29.03.2023



Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

Trade name: Lotpaste SP2200 Sn63Pb37

Printing date 29.03.2023

(Contd. of page 6)

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN3082 · 14.2 UN proper shipping name · ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (lead powder [particle diameter < 1 mm]) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (lead powder [particle diameter < 1 mm], 2-ETHYLHEXYLAMINE), MARINE POLLUTANT · IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (lead powder [particle diameter < 1 mm]) 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles. · Label 9 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Hazard identification number (Kemler code): 90 · EMS Number: F-A,S-F Stowage Category Α · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Transport category 3 Tunnel restriction code (-) · IMDG · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LEAD POWDER [PARTICLE DIAMETER < 1 MM]), 9, III

> GB (Contd. on page 8)



Page 8/9

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

Printing date 29.03.2023

Trade name: Lotpaste SP2200 Sn63Pb37

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

- lead powder [particle diameter < 1 mm]
- 2-(2-hexyloxyethoxy)ethanol

Hazard statements

- H318 Causes serious eve damage.
- H360FD-H362 May damage fertility. May damage the unborn child. May cause harm to breast-fed children.
- H372 Causes damage to the central nervous system, the kidneys and the blood through prolonged or repeated exposure.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements				
P201	Obtain special instructions before use.			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P263	Avoid contact during pregnancy and while nursing.			
P270	Do not eat, drink or smoke when using this product.			
P273	Avoid release to the environment.			
P280	Wear protective gloves / eye protection.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and			
	easy to do. Continue rinsing.			
P310	Immediately call a doctor.			
P308+P313	IF exposed or concerned: Get medical advice/attention.			
P314	Get medical advice/attention if you feel unwell.			
P391	Collect spillage.			
P405	Store locked up.			
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.			

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category E1 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

National regulations:

· Substances of very high concern (SVHC) according to UK REACH

CAS: 7439-92-1 lead powder [particle diameter < 1 mm]

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- Toxic if swallowed. H301
- H302 Harmful if swallowed.
- Toxic in contact with skin. H311
- H312 Harmful in contact with skin.



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.3 (replaces version 1.2)

Revision: 29.03.2023

(Contd. of page 8)

Page 9/9

Trade name: Lotpaste SP2200 Sn63Pb37

- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.

Printing date 29.03.2023

- H360FD May damage fertility. May damage the unborn child.
- H362 May cause harm to breast-fed children.
- Causes damage to organs through prolonged or repeated exposure. H372
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH201A Warning! Contains lead.

· Department issuing SDS: Product Safety Department

Contact: Hr. Dörr

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Repr. 1A: Reproductive toxicity - Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

GB