

Page 1/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

1 Identification

· Product identifier

· Trade name: <u>Loetdraht HS10 Ecoloy TC</u> Loetdraht HS10 Ecoloy TC300

Loetdraht HS10 Flowtin TC

Loetdraht HS10 Flowtin TC300

<u>Loetdraht HS10 Flowtin+ TC</u> <u>Loetdraht HS10 Flowtinq+ TC300</u>

Loetdraht HS10 Fair Flowtin TC

Loetdraht HS10 Fair Flowtin+ TC

- · Application of the substance / the mixture Brazing alloy
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Stannol GmbH & Co. KG Haberstrasse 24 D-42551 Velbert

+49 (0) 2051 3120 332 sdb@stannol.de

- · Information department: Product Safety Department
- Emergency telephone number:

8:00 am - 5:00 pm (CET) +49 (0) 2051 3120 332

+1 (307) 899 3845

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Rosin

Hazard statements

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)





Page 2/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowting+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 1)

· Other hazards

Inhalation of vapors that are released during the soldering process should be avoided. Flux fumes will irritate nose, throat and lungs and may cause allergic reaction (asthma) after prolonged or repeated exposure. Therefore, we recommend the usage of fume extractions with appropriate filters.

Always wash your hands carefully with soap and water after handling the product before eating, drinking and smoking. Do not heat the soldering materials above 500 °C.

Keep out of reach of children.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 7440-31-5 EINECS: 231-141-8 CAS: 8050-09-7 Rosin EINECS: 232-475-7

CAS: 7440-50-8 Copper, solid

EINECS: 231-159-6

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

US



Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowtinq+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

CAS: 7440-31-5 tin	6 mg/m³
CAS: 8050-09-7 Rosin	72 mg/m ³
CAS: 7440-50-8 Copper, solid	3 mg/m³

PAC-2:

CAS: 7440-31-5 tin	67 mg/m³
CAS: 8050-09-7 Rosin	790 mg/m ³
CAS: 7440-50-8 Copper, solid	33 mg/m ³

PAC-3:

CAS: 7440-31-5 tin	400 mg/m ³
CAS: 8050-09-7 Rosin	1,500 mg/m ³
CAS: 7440-50-8 Copper, solid	200 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Storage class: 11
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 4)



Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowtinq+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 3)

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 7440-31-5 tin

PEL (USA) Long-term value: 2 mg/m³

metal

REL (USA) Long-term value: 2 mg/m³

TLV (USA) Long-term value: 2* mg/m³

metal, *inh. fraction

CAS: 8050-09-7 Rosin

TLV (USA) Long-term value: 0.001* mg/m3

*inhalable fraction, DSEN, RSEN

CAS: 7440-50-8 Copper, solid

PEL (USA) Long-term value: 1* 0.1** mg/m³

as Cu *dusts and mists **fume

REL (USA) Long-term value: 1* 0.1** mg/m³

as Cu *dusts and mists **fume

TLV (USA) Long-term value: 1* 0.2** mg/m³

*dusts and mists; **fume; as Cu

- \cdot Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:



Protective gloves

Rubber gloves

Synthetic gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 5)



Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowtinq+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Wire Color: Grey

Odor: Characteristic
 Odor threshold: Not determined.
 pH-value: Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.
Undetermined.

Not applicable.

Flammability (solid, gaseous):

Decomposition temperature:
Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapor pressure:
Not applicable.

Density:
Not determined.
Relative density
Not determined.
Vapor density
Not applicable.
Evaporation rate
Not applicable.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

VOC content: 0.00 % **Solids content:** 100.0 %

(Contd. on page 6)



Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowtinq+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- $\cdot \mbox{\bf Persistence and degradability} \ \mbox{No further relevant information available}.$
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 7)



Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowtinq+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 6)

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· UN-Number

· DOT, ADN, IMDG, IATA not regulated

· UN proper shipping name

· DOT, ADN, IMDG, IATA not regulated

· Transport hazard class(es)

· DOT, ADN, IMDG, IATA

· Class not regulated

· Packing group

DOT, IMDG, IATA not regulated
 Environmental hazards: Not applicable.
 Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

UN "Model Regulation":

not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

CAS: 7440-50-8 Copper, solid

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.



Page 8/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowting+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 7)

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

CAS: 7440-50-8 Copper, solid

D

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

· Hazard statements

May cause an allergic skin reaction.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product Safety Department
- · Contact: Hr. Dörr
- $\cdot \, \textbf{Date of preparation} \, / \, \textbf{last revision} \, \, 04/26/2023$
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)



Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: Loetdraht HS10 Ecoloy TC

Loetdraht HS10 Ecoloy TC300 Loetdraht HS10 Flowtin TC Loetdraht HS10 Flowtin TC300 Loetdraht HS10 Flowtin+ TC Loetdraht HS10 Flowting+ TC300 Loetdraht HS10 Fair Flowtin TC Loetdraht HS10 Fair Flowtin+ TC

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

VOC: Volatile Organic Compounds (USA, EÙ) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Sensitization - Skin 1: Skin sensitisation – Category 1

US